



LIGHT
AND
HANDY

EASY
CHANGE

EASY
OPERATION

EASY
MAINTENANCE

Lab water purification systems

design for general laboratory application

您~絕對值得擁有自己的超純水系統!



Model	EcoQ-Ultra	EcoQ-Superb	EcoQ-Combo
Product Water Quality			
Type III flow rate	—	—	20L / Hr $\pm$ 10%
Type I flow rate	1L / min $\pm$ 10%	2L / min $\pm$ 10%	0.6L / min $\pm$ 10%
Resistivity	18.2M Ω .cm @ 25°C	18.2M Ω .cm @ 25°C	18.2M Ω .cm @ 25°C
Total Organic Carbon, TOC	<30 ppb	<10 ppb	<10 ppb
Total Silica	<3 ppb	<3 ppb	<3 ppb
Microorganisms	<5 CFU/ml	<1 CFU/ml	<1 CFU/ml
Particles	<2 μ m	<2 μ m	<2 μ m
Endotoxin (With UF filter)	<0.001 EU/ml	<0.001 EU/ml	<0.001 EU/ml
pH	neutral	neutral	neutral

System Information	EcoQ-Ultra	EcoQ-Superb	EcoQ-Combo
Feed water temperature	5~40°C	5~40°C	5~40°C
Feed water pressure	15~90PSI	15~90PSI	15~90PSI
Voltage	110V	110V	110V
Frequency	60Hz	60Hz	60Hz
Net Weight	13 kg	13 kg	13 kg
Dimensions (H x W x D)	420 x 220 x 430 mm	420 x 220 x 430 mm	420 x 220 x 430 mm

EcoQ Ultra Pure Water System providing high-quality and stable pure water. Accord with  Type I & Type III quality specifications, and certified by .

Ultra Pure Water System